

Sumiliteresin® PR-16 I

Phenolic

SBHPP

Описание материалов:

SUMILITERESIN® PR-16 I is a standard straight novolak type powder. It is generally apply for Brake Lining, Disc Pad and clutch facing.

Characteristics

SUMILITERESIN® PR-16 I is a powder phenolic resin with good friction properties, good process, and other merit in production of friction.

SUMILITERESIN® PR-16 I has low Free phenol, hexamine content about 9% and middle molecular weight. By these properties, it will improve stability friction coefficient, hardness and wear rate.

Главная Информация		
Характеристики	Обрабатываемость, хорошая Средний Молекулярный вес	
Внешний вид	Белый Желтый	
Формы	Порошок	
Физический	Номинальное значение	Единица измерения
Длина потока (125°C)	2.40 - 4.60	cm
Анализ сита-106 мм		%
Тепловой	Номинальное значение	Единица измерения
Температура плавления	93.0 - 105	°C
Uncured Properties	Номинальное значение	Единица измерения
Gel Time (150°C)	1.4 - 2.1	min

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай



WeChat