

Fainplast PVC MGS 80/G

Flexible Polyvinyl Chloride

Fainplast Compounds S.r.l

Описание материалов:

Fainplast PVC MGS 80/G is a Flexible Polyvinyl Chloride product. It can be processed by injection molding and is available in Africa & Middle East, Europe, Latin America, or North America. Applications of Fainplast PVC MGS 80/G include medical/healthcare and electrical/electronic applications. Primary characteristic: sterilizable.

Главная Информация			
Характеристики	Радиационный стерилизуемый		
Используется	Разъемы		
	Медицинские/медицинские приложения		
Рейтинг агентства	EP монография 3.1.1.2		
Метод обработки	Литье под давлением		
Физический	Номинальное значение	Единица измерения	Метод испытания
Плотность	1.23	g/cm ³	ISO 1183
Твердость	Номинальное значение	Единица измерения	Метод испытания
Твердость по суше (Shore A)	80		ISO 868
Механические	Номинальное значение	Единица измерения	Метод испытания
Tensile Stress (Break)	> 16.0	MPa	ISO 527-2
Растяжимое напряжение (Break)	> 340	%	ISO 527-2

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай



WeChat