

Sumiliteresin® PR-51794 I

Phenolic

SBHPP

Описание материалов:

SUMILITERESIN® PR-51794 I is a standard straight novolak type powder form phenolic resin.

Characteristics

SUMILITERESIN® PR-51794 I is a powder form phenolic resin which has short flow, high hexamine content [13%] and high molecular weight.

For Friction Material : high hardness and high heat resistance.

For Bonded Abrasive : well balanced resistance with cutting-sharpness and very good for wear life. It's preferable for snagging wheel.

| Главная Информация | | |
|-----------------------|---|-------------------|
| Характеристики | Высокая Молекулярная масса Хорошая стойкость к истиранию Теплостойкость, высокая Высокая твердость | |
| Внешний вид | Белый Желтый | |
| Формы | Порошок | |
| Физический | Номинальное значение | Единица измерения |
| Длина потока (125°C) | 1.20 - 2.90 | cm |
| Анализ сита-106µm | | % |
| Тепловой | Номинальное значение | Единица измерения |
| Температура плавления | 95.0 - 115 | °C |
| Uncured Properties | Номинальное значение | Единица измерения |
| Gel Time (150°C) | 1.2 - 1.8 | min |

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

