

Reon 67GER01

Polyvinyl Chloride Homopolymer

Reliance Industries Limited

Описание материалов:

67GER01 is a medium molecular weight suspension type PVC resin suitable for rigid extrusion products. It is specially recommended for rigid pipes & conduits, rigid profiles, rigid sheets, unplasticised tubular film, etc. Its combination of medium molecular weight with high apparent bulk density makes it suitable for easy processing at high output rate, still maintaining the high mechanical properties. Its balanced heat loss property does not allow static to develop and reduces the flow time. At the same time the resin contains minimum volatiles. The narrow range of porosity of 67GER01 makes it easy to maintain a uniform fusion point at constant lubricant level. Uniform coarseness of the grains of this resin results in easy bulk handling, minimum requirement of lubricant and more uniform fluxing in the extruder.

Главная Информация	
Характеристики	Хорошая технологичность Высокий поток Гомополимер Средний Молекулярный вес
Используется	Пленка Трубопроводы Профили Лист
Рейтинг агентства	10151
Метод обработки	Выдувная пленка Каландрирование Экструзия

Физический	Номинальное значение	Единица измерения	Метод испытания
Видимая плотность	0.55	g/cm ³	ASTM D1895
K-Value ¹	67.0		
Внутренняя вязкость	0.92		ASTM D1243
Распределение размеров частиц			ASTM D1921
Retention on ASTM 40 mesh	< 0.10	%	
Retention on ASTM 60 mesh	< 5.0	%	
Through ASTM 140 mesh	< 25	%	
Потеря тепла	< 0.30	%	ASTM D3030
Темная Смола-Для смолы 100 г	< 10.0	count/g	
Время потока	< 25.0	sec	ASTM D1895
Пористость-Доп	0.210 to 0.290	cm ³ /g	ASTM D3367

Остаточный винилхлорид мономер	< 2	ppm	ASTM D3749
--------------------------------	-----	-----	------------

NOTE

1. @ 1% in cyclohexanone

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

