

NANCAR® 1022

Acrylonitrile Butadiene Rubber

Nantex Industry Co., Ltd.

Описание материалов:

NANCAR® 1022 is a medium high acrylonitrile butadiene copolymer, with good oil resistance. It is a crosslinked type copolymer containing sufficient non-staining stabilizers for normal storage condition.

Suggested usages include applications in automotive door panel sheet, crash pad sheet, wire and cable insulation, extruded profiles and so on.

Modifying resins (EX. PVC).

Главная Информация			
Добавка	Неуказанный стабилизатор		
Характеристики	Сополимер Маслостойкий		
Используется	Автомобильные Приложения Изоляция Профили Лист Применение проводов и кабелей		
Формы	Гранулы		
Метод обработки	Экструзия		
Физический	Номинальное значение	Единица измерения	Метод испытания
Удельный вес	0.980	g/cm ³	
Вязкость Mooney (ML 1+4, 100°C)	40	MU	ASTM D1646
Содержание акрилонитрила-Скрепленный	33.0	%	Internal Method
Содержание золы	0.60	%	Internal Method
Содержание геля	75	%	Internal Method
Стабилизатор	Non-staining		
Потеря тепла	0.30	%	ASTM D5688

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

