Geon™ Vinyl Flexible XV-3766

Flexible Polyvinyl Chloride

PolyOne Corporation

Описание материалов:

Geon™Vinyl Flexible XV-3766 is a flexible polyvinyl chloride product. It can be processed by extrusion or injection molding and is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific. Typical application areas are: food contact applications. The main characteristics are: accessible food.

Главная Информация	
Характеристики	Соответствие пищевого контакта
Рейтинг агентства	FDA пищевой контакт, не Номинальный
Внешний вид	Прозрачный/прозрачный
Формы	Частицы
Метод обработки	Экструзия
	Литье под давлением

Физический	Номинальное значение	Единица измерения	Метод испытания
Удельный вес	1.22	g/cm³	ASTM D792
Твердость	**Номинальное значение**	**Единица измерения**	**Метод испытания**
Твердость дюрометра (Shore A, 10 sec)	78		ASTM D2240
Механические	**Номинальное значение**	**Единица измерения**	**Метод испытания**
Прочность на растяжение [1]			ASTM D638
Fracture	17.2	MPa	ASTM D638
100% strain	10.3	MPa	ASTM D638
Удлинение при растяжении [2] (Break)	350	%	ASTM D638
Тепловой	**Номинальное значение**	**Единица измерения**	**Метод испытания**
Температура ломкости	-37.2	°C	ASTM D746

Дополнительная информация

□□:□□□21□□□□.□□□□□□,□□□“□□□□□□□□□□”.□□□□□□□□□□□□□□□□□□□

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

WeChat