

## POLYFLON™ M-18F

Polytetrafluoroethylene

Daikin Fluorochemicals (China) Co., Ltd.

### Описание материалов:

POLYFLON PTFE M-series is a granular powder for compression molding. As melt viscosity is extremely high, it cannot be used for molding applied to general plastic. Therefore basically at first it is compressed in the mold and is fused by sintering over its melting point. Various molding methods are developed.

There are many types of POLYFLON PTFE to be applied the methods, conditions in mold processing and application.

#### Features

Because of the small particle size and sharp particle size distribution, molding articles show excellent properties. Suitable for compound with various fillers as the base powder.

Главная Информация		
Характеристики	Высокая вязкость	
Формы	Порошок	
Метод обработки	Прессформа сжатия	
Физический	Номинальное значение	Единица измерения
Видимая плотность	0.33	g/cm <sup>3</sup>
Средний размер частиц	25	µm

\* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

### Свяжитесь с нами

## Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

