

# Hydroxy-Purge 15C

Thermoplastic

InChem Corp.

## Описание материалов:

InChemRez Hydroxy-Purge 15C is a thermoplastic organic resin alloyed with inert minerals designed to efficiently and effectively clean conventional reciprocating screw molding systems. The organic thermoplastic resin is characterized as a tough and ductile thermoplastic amorphous polymer having excellent thermal stability and wetting characteristics.

Hydroxy-Purge 15C offers an intermediate level of "scrubbing" characteristics for use at temperatures between 350 and 560°F. Typically, four pounds per diameter inch of Hydroxy-Purge 15C is recommended for standard cleaning (refer to InChem publication "Instructions For Use In Injection Molding Equipment" for complete list of parameters and use suggestions).

Hydroxy-Purge 15C is highly effective because:

the proprietary formulation works under high agitation to dislodge contaminants;

formulation contains resins and agents to wet out pigments efficiently resulting in short cleaning cycles;

of less adhesion to internal metal surfaces.

FDA Status of Hydroxy-Purge 15C

InChemRez Hydroxy-Purge 15C is intended for use as extruder purge compounds. The resinous portion of Hydroxy-Purge 15C is compliant with numerous FDA requirements including coatings for direct and indirect food contact (21CFR175.300), adhesives (21CFR175.105), and as a component for articles intended for repeated use producing, manufacturing, packing, processing, preparing, treating, packaging, transporting, or holding food (21CFR177.2280).

The inorganic portion of Hydroxy-Purge 15C is compliant with the guidelines of 21CFR182.2727, i.e., Generally Recognized As Safe (GRAS).

Safety and Handling

Hydroxy-Purge 15C is sold in 45 kg drums, 114 kg drums, and 500 kg gaylord. The compound is indefinitely stable in unopened containers when stored at normal temperatures.

Consult the product MSDS for additional information on properties, hazards, and handling.

For safe use information of Hydroxy-Purge 15C and other InChem cleaning compounds read "Instructions For Use In Injection Molding Equipment" available from InChem customer service by fax and/or PDF file.

Главная Информация			
Характеристики	Термическая стабильность, хорошая Хорошая прочность Аморфный Пластичность		
Используется	Очистительная смесь		
Рейтинг агентства	Управление по санитарному надзору за качеством пищевых продуктов и медикаментов 21 CFR 175,105 Управление по санитарному надзору за качеством пищевых продуктов и медикаментов 21 CFR 175,300 Управление по санитарному надзору за качеством пищевых продуктов и медикаментов 21 CFR 177,2280 Управление по санитарному надзору за качеством пищевых продуктов и медикаментов 21 CFR 182,2727		
Формы	Частицы		
Метод обработки	Литье под давлением		
Физический	Номинальное значение	Единица измерения	Метод испытания
Видимая плотность	0.72	g/cm <sup>3</sup>	ASTM D1895
Дополнительная информация			
Use rate: 4 pounds per inch (diameter)Color: gray-brown			

\* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

## Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

