

Siloxane Masterbatch MB40-006

Siloxane Polymer (UHMW)

Multibase, A Dow Corning Company

Описание материалов:

DESCRIPTION

DOW CORNING MB40006 Masterbatch is a pelletized formulation containing 40% of an ultra-high molecular weight (UHMW) siloxane polymer dispersed polyoxymethylene (acetal) copolymer. It is designed to be used as an additive in most acetal compatible systems to impart benefits such as processing improvements and modification of surface characteristics.

Liquid siloxane plastic additives have been used for several years to improve the lubricity and flow of thermoplastics. They are effective in this role although some difficulties have been experienced in the incorporation of liquids into thermoplastic melts without the use of specialized equipment. It has also been difficult to produce masterbatches with greater than 20% liquid siloxane because of processing difficulty and bleed problems.

The DOW CORNING® MB Series Masterbatches address these problems by supplying a high concentration of an ultra-high molecular weight (UHMW) siloxane as a dispersion in a dry pellet form in a variety of thermoplastics.

BENEFITS

When added to acetal or similar thermoplastics at 0.2% to 2.0%, improved processing and flow of the resin is expected, including better mold filling, less extruder torque, internal lubrication, mold release, and faster throughput. At higher addition levels, 2% to 10%, improved surface properties are expected, including lubricity, slip, lower coefficient of friction, and greater mar and abrasion resistance.

The DOW CORNING MB Series Masterbatches are expected to give improved benefits compared to conventional lower molecular weight siloxane additives, e.g., less screw slippage, improved release, a lower coefficient of friction, fewer paint and printing problems, and a broader range of performance capabilities.

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

FOOD CONTACT

DOW CORNING MB40006 Masterbatch is suitable for use as a slip or release agent in the production of the basic polymer or finished food contact article in compliance with US FDA regulation 21 CFR 177.2470. The acetal portion of DOW CORNING MB40006 Masterbatch complies with 177.2470 and the siloxane portion complies with 181.28.

This document is available from your local Dow Corning representative.

HOW TO USE

DOW CORNING MB Series Masterbatches may be processed in the same way as the thermoplastics on which they are based. Sufficient DOW CORNING MB40006 Masterbatch should be blended with virgin polymer pellets to give the desired siloxane level in the final product. DOW CORNING MB40006 Masterbatch pellets can be added during compounding in a single screw extruder or added at the feed hopper during injection molding or extrusion.

Главная Информация

Добавка	Пресс-форма
	Силиконовая смазка
	Комбинация
Характеристики	Отличная Печатающая способность
	Приемлемый пищевой контакт
	Хорошая стойкость к истиранию
	Хороший поток
	Хороший выпуск пресс-формы
	Хорошая технологичность
	Хорошая поверхность
	Хорошая износостойкость
Низкое трение	

Смазка
Болезненный
Устойчивость к царапинам
Комбинация
Сверхвысокий Молекулярный вес

Используется Смешивание
Уплотнение
Модификация пластмасс

Рейтинг агентства Управление по санитарному надзору за качеством пищевых продуктов и медикаментов 21 CFR 177,247

Внешний вид Кремово-белый

Формы Гранулы

Метод обработки Уплотнение
Экструзия
Литье под давлением

Дополнительная информация	Номинальное значение	Единица измерения
Органическая смола	Polyoxymethylene (acetal) copolymer, MI 27	
Содержание силоксан	40	%
Предлагаемый уровень использования	0.20 to 10	%

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

