

Dyna-Purge® X

Proprietary

Dyna-Purge, division of Shuman Plastics

Описание материалов:

Designed for Profile, Sheet, Cast Film & Compounding

DYNA-PURGE X is a non-abrasive, non-chemical engineered thermoplastic purging compound, designed to have a natural flow through the extruder. An advanced formulation with dual action scrubbing expands into negative flow areas, loosening and removing degraded material. This grade is designed for extruders that process tubing or pipe, sheet, other profile applications, as well as cast film and compounding.

FEATURES & BENEFITS:

Excellent for color changes, resin changes, preventative machine maintenance, and before manual cleaning

Developed for purging through the barrel, die head, and other downstream equipment with a minimum clearance of .025 inch (.65 mm)

Effective through a wide temperature range 320°F to 575°F (160°C to 302°C)

Easy to use - no process adjustment necessary - use at the resident resin processing temperature and RPM speed

Non-abrasive, non-melting but softening thermoplastic, which thoroughly loosens carbonized and degraded resin, allowing it to be flushed out of the system

Safe, non-hazardous, with no chemicals - ingredients are FDA compliant

Heat stable - recommended during shutdown and start-up

Low "cost per purge" - only small quantity is needed to be effective

No mixing required, simply use "as is"

Unlimited shelf life

Главная Информация

Используется	Очистительная смесь
Рейтинг агентства	FDA не рассчитан
Формы	Частицы
Метод обработки	Экструзионная смесь Экструзия Литая пленка Экструзионный лист Экструзионное формование профиля

Дополнительная информация

Applications: Extrusion - profile, sheet, cast film & compounding

Temperature Range: 320 - 575°F (160 - 302°C)

Types of Resins: All

Minimum Clearance: 0.025 inch or 0.65 mm

Amount of Purge: 1 to 2 times barrel capacity (actual amount needed depends on machine conditions)

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

