

Dyna-Purge® M

Proprietary

Dyna-Purge, division of Shuman Plastics

Описание материалов:

Most versatile & widely used in the Plastics Industry

DYNA-PURGE M is a versatile non-abrasive, non-chemical engineered thermoplastic purging compound, formulated to flow naturally through the barrel and hot runner system of the injection molding machine, as well as extrusion equipment. Two non-melting but softening thermoplastic ingredients scrub, while an exclusive proprietary additive helps to remove any contamination without leaving a residue.

FEATURES & BENEFITS:

Developed for color changes, resin changes, preventative machine maintenance and before manual cleaning

Excellent for purging through hot runner systems with a minimum clearance of 0.030 inch (0.75 mm)

Effective through a wide temperature range 350°F to 600°F(177°C to 315°C)

Easy to use - no process adjustment necessary - use at the resident resin processing temperature and RPM speed

Non-abrasive, non-melting but softening thermoplastic, which thoroughly loosens carbonized and degraded resin, allowing it to be flushed out of the system

Safe, non-hazardous, with no chemicals - ingredients are FDA compliant

Heat stable - recommended during shutdown and start-up

Low "cost-per-purge" - only small quantity needed to be effective

No mixing required - simply use "as is"

Unlimited shelf life

Главная Информация	
Используется	Очистительная смесь
Рейтинг агентства	FDA не рассчитан
Формы	Частицы
Метод обработки	Экструзионная смесь
	Экструзия
	Экструзионное выдувное формование
	Экструзионный лист
	Экструзионное формование профиля
	Литье под давлением

Дополнительная информация

Applications:

Injection - cold and hot runners

Extrusion - profile, sheet, compounding & blow molding

Temperature Range: 350 - 600°F (177 - 315°C)

Types of Resins: All

Minimum Clearance: 0.030 inch or 0.75 mm

Amount of Purge: 1 to 2 times barrel capacity (actual amount needed depends on machine conditions)

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами



Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

