

## Lusin® Clean 1500

Unspecified

Chem-Trend L.P.

### Описание материалов:

High concentrated purging compound for screws, cylinders, nozzles and hotrunner systems during processing of polycarbonates

Benefits:

Especially dedicated for the cleaning of polycarbonate

Concentrated: low consumption - economical

No smell during application

No contamination of the following parts

Removes residues and encrustations

Suitable for hotrunner systems

No generation of milky traces

Lusin® Clean 1500 is a high concentrated purging compound that is specially developed for the processing of polycarbonate. The compound consists of high grade plastics with high efficient cleaning additives and doesn't contain any abrasives. The product is completely miscible with polycarbonate and doesn't generate any milky traces.. Lusin® Clean 1500 can be used at processing temperatures up to 350°C.

Application:

Lusin® Clean 1500 is suitable for colour and material change as well as for removal of black spot contaminations and carbon residues especially on transparent parts.

We recommend the following cleaning procedure::

1. Prepare a mixture of PC containing 25% of Lusin Clean 1500 (see dosing table)
2. Empty cylinder
3. Fill the mixture into the hopper
4. Fill the cylinder with the plasticized mixture. Stop the screw for 3 - 5 minutes in case of strong and resistant contaminations.
5. Purge the cleaning mixture or in case of cleaning the hotrunner system inject into the mould
6. Refill cylinder with new material
7. Restart production

In case of changing from polycarbonate to other resins like ABS, PP or PA the processing temperatures should be adjusted to the new material after the purge was performed. On restart of the following material the processing temperatures should not be below 250°C.

Dosage Table:

Dosing table for the cleaning of screw and cylinder (approx. values):

Screw diameter// Recommended quantity of Lusin® Clean 1500// Recommended quantity of neutral PC

30 mm// 0,1 kg// 0,3 kg

40 mm// 0,2 kg// 0,6 kg

60 mm// 0,4 kg// 1,2 kg

80 mm// 0,7 kg// 2,1 kg

100 mm// 1,3 kg// 3,9 kg

120 mm// 2,5 kg// 7,5 kg

Storage / Handling: For further information on storage, handling hazards etc please refer to the safety data sheet..

Storage: Store in indoor area at room temperature.

Shelf life: 2 years

Packaging: 20kg in a tin plated container 7.5 kg in a tin plated container

### Главная Информация

Характеристики	Низкий и без запаха
Используется	Очищающее соединение
Формы	Гранулы

\* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

## Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

