

Ketjenflex® MS 80

Plasticizer Additive

Axcentive SARL

Описание материалов:

KETJENFLEX® MS 80 is a toluene sulfonamide based plasticizing co-resin dissolved in 20% butylacetate. It is used in Nail lacquers, Coatings, Adhesives and Inks.

Description and Application

KETJENFLEX® MS 80 is the liquid version of KETJENFLEX® MH the most widespread plasticizing resin for nitrocellulose based nail lacquers.

KETJENFLEX® MS 80 has the advantage that it can be easily poured into formulation during the production process.

KETJENFLEX® MS 80 imparts improved adhesion and wear properties and generally provides the lacquer system with a shiny glossy appearance.

KETJENFLEX® MS 80 can also be used as plasticizing resin in solvent borne coating and ink formulations. Here KETJENFLEX® MS 80 acts as a non-migratory plasticizing co-resin improving the adhesion and gloss of the system.

Applications:

Nail lacquers

Nitrocellulose coatings

Cellulose acetate formulations

Printing inks

Главная Информация

Additives Physical	Номинальное значение	Единица измерения
Additive Concentration	> 78	%
State at Room Temperature	Liquid	
Boiling Temperature	127	°C
Chemical Description	Toluene Sulfonamide	

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай



WeChat