Vistamaxx™ 8880

Performance Polymer

ExxonMobil Chemical

Описание материалов:

Vistamaxx 8880 is primarily composed of isotactic propylene repeat units with random ethylene distribution, and produced using ExxonMobil's proprietary metallocene catalyst technology. It has very low viscosity that enables its use in hot melt adhesives (HMAs) and as a process aid or viscosity modifier in extrusion and injection molding applications providing enhanced flow characteristics that can lead to efficiency and cycle time improvements.

Главная Информация	
Используется	Композитный Клей
Формы	Частицы
Метод обработки	Композитный Экструзия Литье под давлением

Твердость	Номинальное значение	Метод испытания
Твердость дюрометра (Shore C)	53	ASTM D2240

Дополнительная информация

For handling and safety information, consult the appropriate Safety Data Sheet.ExxonMobil Test Methods, some of which were developed from ASTM test methods, are available upon request.It is the responsibility of the user to ensure that the composition containing our product meets the limitations of relevant regulations. Please contact Customer Service for the official food law certificates which provide more detailed information.

Юридическое заявление

□□□□□□□□□□□,□□□□□□□.□□□□□□□□□□□□□,□□□□□□□□□□□,□□□□□□□□□□□□□□□□□

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

WeChat