

Artenius MB01

Polyethylene Terephthalate

Artenius

Описание материалов:

Artenius MB01 is a copolymer of PET (Polyethylene-Terephthalate) in amorphous state, delivered in resin pellets. This resin has a high blue concentration and very good dispersion. The material presents low viscosity and moderate crystallization speed. It can be used as a colour enhancer additive for PET or recycled resins.

Главная Информация			
Характеристики	Аморфный Сополимер Диспергируемый Приемлемый пищевой контакт Низкая вязкость		
Используется	Концентраты цветов		
Рейтинг агентства	EC 94/62/EC EC без 10/2011		
Формы	Гранулы		
Физический	Номинальное значение	Единица измерения	Метод испытания
Видимая плотность	0.76	g/cm ³	
Viscosity Number (Reduced Viscosity)	56.0 to 60.0	ml/g	ISO 1628
Цвет b	-11.0 to -7.00		ASTM D6290
Color L	< 40.0		ASTM D6290
Влага	< 0.30	%	
Вес-Из 20 чипов	320.0	mg	
Типичная температура формования	270 to 290	°C	
Тепловой	Номинальное значение	Единица измерения	
Температура плавления	245 to 255	°C	

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

