

Vinnolit® E 80 TT

Polyvinyl Chloride Homopolymer

Vinnolit GmbH & Co. KG

Описание материалов:

Vinnolit E 80 TT is an emulsion type paste-making homopolymer having a fine particle size. It is giving low viscosity plastisols with an excellent viscosity stability.

At medium plasticizer concentrations, pastes exhibit an almost newtonian rheology across a wide shear range.

Vinnolit E 80 TT is recommended for the production of transparent top coats for CV-flooring, as well as for filled and unfilled rigid to semi-rigid topcoats.

Главная Информация			
Используется	Напольное покрытие		
Рейтинг агентства	EC 1907/2006 (REACH)		
Метод обработки	Пластик		
Физический	Номинальное значение	Единица измерения	Метод испытания
Видимая плотность	0.40	g/cm ³	ISO 60
K-Value	80.0		ISO 1628-2
Viscosity Number (Reduced Viscosity)	169.0	ml/g	ISO 1628
Содержание эмульгатора	Low		
Распределение размеров частиц ¹	< 3.0	%	ISO 4610
Летучее вещество	< 0.50	%	ISO 1269

NOTE

1. retained on 0.063 mm screen

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

