

## Vinnolit® E 74 CC

Polyvinyl Chloride Homopolymer

Vinnolit GmbH & Co. KG

### Описание материалов:

Vinnolit E 74 CC is a fine-particle, paste-making emulsion homopolymer giving plastisols with a medium viscosity and good shelf life. Pastes with a medium plasticizer content are pseudoplastic over the entire shear range.

Vinnolit E 74 CC is a special grade suitable for automotive applications such as foam and top coats in vacuum-thermoformed artificial leather with good emboss retention.

Главная Информация			
Используется	Автомобильные Приложения Пена		
Рейтинг агентства	EC 1907/2006 (REACH)		
Метод обработки	Пластик		
Физический	Номинальное значение	Единица измерения	Метод испытания
Видимая плотность	0.42	g/cm <sup>3</sup>	ISO 60
K-Value	74.0		ISO 1628-2
Viscosity Number (Reduced Viscosity)	141.0	ml/g	ISO 1628
Содержание эмульгатора	Medium		
Распределение размеров частиц <sup>1</sup>	< 3.0	%	ISO 4610
Летучее вещество	< 0.50	%	ISO 1269
Запотевание <sup>2</sup>	< 5.0E-4	g	DIN 75201B
NOTE			
1.	retained on 0.063 mm screen		
2.	Gravimetric		

\* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

## Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

