

PIVINEL™ KAZ-32

Polyvinyl Chloride

HELLENIC CABLES S.A.

Описание материалов:

Description: PVC based compounds for outer sheaths in flame retardants power cables working in polar conditions (-45°C)

Specifications:

i) IEC 92-359 TYPE ST1&ST2

ii) IEC 332-3 Category C flame retardant cables working in low temperatures -45°C

Packaging: In PE bags of 25 kg or in big bags of approximately 1000 kg

Types of cables where it can be used: Armored flame retardant power cables for polar conditions (-45°C) combined with PIVINEL KAZ-12 for inner sheath.

Главная Информация		
Характеристики	Огнестойкий Низкая термостойкость	
Используется	Применение проводов и кабелей	
Метод обработки	Экструзия	
Физический	Номинальное значение	Единица измерения
Удельный вес	1.46	g/cm ³
Экструзия	Номинальное значение	Единица измерения
Зона цилиндра 1 темп.	165	°C
Зона цилиндра 2 температура.	165	°C
Зона цилиндра 3 темп.	170	°C
Зона цилиндра 4 темп.	170	°C
Зона цилиндра 5 темп.	175	°C
Цилиндрическая Зона 6 темп.	175	°C
Зона цилиндра 7 температура.	165	°C
Температура головы	165	°C

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

