

Altuglas® BS 440

Polymethyl Methacrylate Acrylic

Altuglas International of Arkema Inc.

Описание материалов:

ALTUGLAS®BS 440 is a methacryliccopolymer of medium molecular weight with acid functionality, available in the form of solid beads.

ALTUGLAS®BS 440 has good solubility and compatibility: it can be used as Binder in resins and solvent coatings.

ALTUGLAS®BS 440 is recommended as component in low-profile additives for Unsaturated Polyester Curable Resins, especially for SMC application.

Главная Информация		
Характеристики	Сополимер	
	Средний Молекулярный вес	
Используется	Связыватель	
	Нанесение покрытия	
Формы	Сферы	
Физический	Номинальное значение	Единица измерения
Видимая плотность	0.70	g/cm ³
Кислотная ценность	8.00 to 11.00	mg KOH/g
Внутренняя вязкость	0.48 to 0.53	dl/g
Размер частиц	150 to 200	µm
Вязкость		
Solvent (30%w MEK)	450	mPa·s
Solvent (30%w STY)	1200	mPa·s
Остаточный мономер	< 0.50	%
Испарители	< 1.0	%
Тепловой	Номинальное значение	Единица измерения
Температура перехода стекла	100	°C

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

