

Lusin® Clean G 410

Unspecified

Chem-Trend L.P.

Описание материалов:

High Temperature Purging Compound

Benefits

Suitable for all plastics with processing temperatures between 250°C/482°F and 410°C/770°F, e.g., PC, PEEK, PES, PEI, etc.

Low consumption

Rapid cleaning effect

Suitable for use on hot runners

Dosage Table

Screw Diameter // Required quantity of Lusin® Clean G 410

20 mm // 0.4 kg/0.88 lb

30 mm // 0.8 kg/1.76 lb

40 mm // 1.6 kg/3.52 lb

60 mm // 2.8 kg/6.16 lb

80 mm // 5.0 kg/11.0 lb

100 mm // 10.0 kg/22.0 lb

Description

Lusin® Clean G 410 is a granular ready-to-use purging compound for the screws, cylinders and nozzles of thermoplastic injection moulding machines. It is based on high-grade plastics with additives and contains no abrasives.

Lusin® Clean G 410 can be used at operating temperatures in the range between 250°C/482°F and 410°C/770°F and is suitable for cleaning hot runners, particularly with external heaters.

Application Instructions

Applied at the correct operating temperature, Lusin® Clean G 410 removes residues and encrustations on screws, cylinders and nozzles. Cleaning with this product during color change results immediately in clean parts and reduces scrap. The processing procedure is as follows:

1. The required quantity of purging compound can be found in the Dosage Table.
2. Empty cylinder.
3. Fill hopper with Lusin® Clean G 410. Cleaning temperature should be set at the previous materials processing temperature.
4. To minimize odor, use low backpressure to inject the purging compound. To facilitate rapid cooling of the emerging material, it is recommended material be fed into a water bath.
5. Fill new plastic material into hopper. Set new processing temperature. Inject the rest of the purging compound and start normal production

Storage/Handling

Lusin® Clean G 410 has a shelf life of two (2) years and should be stored its in original sealed packing in a dry indoor area. For further information on storage, handling, hazards, please request a copy of Chem-Trend's Material Safety Data Sheet.

Packaging

Lusin® Clean G 410 is available in 25 kg. bags.

Главная Информация

Характеристики	Высокая термостойкость
Используется	Очищающее соединение
Формы	Гранулы
Метод обработки	Литье под давлением

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

