

Dyna-Purge® B

Proprietary

Dyna-Purge, division of Shuman Plastics

Описание материалов:

Designed for Injection and Extrusion Blow Molding

DYNA-PURGE B is a non-abrasive, non-chemical engineered thermoplastic purging compound, formulated to flow naturally through the barrel and accumulator head. A non-melting but softening thermoplastic scrubs the screw and barrel, while the carrier matrix flushes away impurities.

FEATURES & BENEFITS:

Excellent for color changes, resin changes, preventative machine maintenance, and before manual cleaning

Developed for purging through the barrel and die head with a minimum clearance of .025 inch (.65 mm)

Effective through a wide temperature range 320°F to 575°F (160°C to 302°C)

Easy to use - no process adjustment necessary - use at the resident resin processing temperature and RPM speed

Non-abrasive, non-melting but softening thermoplastic, which thoroughly loosens carbonized and degraded resin, allowing it to be flushed out of the system

Safe, non-hazardous, with no chemicals - ingredients are FDA compliant

Heat stable - recommended during shutdown and start-up

Low "cost-per-purge" - only small quantity needed to be effective

No mixing required - simply use "as is"

Unlimited shelf life

Главная Информация

Используется	Очистительная смесь
Рейтинг агентства	FDA не рассчитан
Формы	Частицы
Метод обработки	Выдвунное формование Экструзионное выдвунное формование Литье под давлением

Дополнительная информация

Applications: Blow molding

Temperature Range: 320 - 575°F (160 - 302°C)

Types of Resins: All

Minimum Clearance: 0.025 inch or 0.65 mm

Amount of Purge: 1 to 2 times barrel capacity (actual amount needed depends on machine conditions)

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

