

Vinnolit® P 70 HT

Polyvinyl Chloride Homopolymer

Vinnolit GmbH & Co. KG

Описание материалов:

Vinnolit P 70 HT is a fine grained microsuspension homopolymer, designed for paste-applications. It can be easily converted into a plastisol with low viscosity, moderate pseudo-plastic flow characteristic and excellent shelf-life.

The plastisols made of Vinnolit P 70 HT with a medium plasticizer content exhibit a moderate pseudoplastic rheology with slight dilatancy at high shear rates. The dilatancy can be reduced/eliminated by blending with extender resins, such as Vinnolit C 65 V or Vinnolit C 66 W or with specially emulsion grades.

Vinnolit P 70 HT shows excellent low water absorption characteristics and has outstanding weathering properties combined with a very high thermostability. With this dominant properties it is perfectly useful for outdoor applications, like signs, tarpaulins, awnings, bill-boards, roofing sheets, textile constructions and coil coatings. The product additionally shows an excellent transparency and very low plate out properties, which makes it profoundly suitable for clear-transparent top coats as well as for printed surfaces (advertising).

Главная Информация			
Характеристики	Хорошая термическая стабильность Хорошая устойчивость к погоде Высокая четкость Низкое поглощение воды Низкая вязкость		
Используется	Наружное применение Лист		
Рейтинг агентства	EC 1907/2006 (REACH)		
Метод обработки	Пластик		
Физический	Номинальное значение	Единица измерения	Метод испытания
Видимая плотность	0.35	g/cm ³	ISO 60
K-Value	70.0		ISO 1628-2
Viscosity Number (Reduced Viscosity)	124.0	ml/g	ISO 1628
Содержание эмульгатора	Extremely Low		
Распределение размеров частиц ¹	< 0.30	%	ISO 4610
Летучее вещество	< 0.30	%	ISO 1269

NOTE

1. retained on 0.063 mm screen

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

