

POLYFLON™ M-391S

Polytetrafluoroethylene

Daikin Fluorochemicals (China) Co., Ltd.

Описание материалов:

POLYFLON PTFE M-series is a granular powder for compression molding. As melt viscosity is extremely high, it cannot be used for molding applied to general plastic. Therefore basically at first it is compressed in the mold and is fused by sintering over its melting point. Various molding methods are developed.

There are many types of POLYFLON PTFE to be applied the methods, conditions in mold processing and application.

Features

Good flowability, small particle size, sharp particle size distribution and low electrostatic charging property. Its molding articles have extremely smooth surfaces. Suited for thin-walled mold gap and iso static molding because of the excellent filling property. Can be used in the case of lack of press ability of the mold machine, for example, large size sheet, from one side press, etc.

Главная Информация		
Характеристики	Хороший поток Высокая вязкость	
Используется	Лист	
Формы	Порошок	
Метод обработки	Прессформа сжатия	
Физический	Номинальное значение	Единица измерения
Видимая плотность	0.80	g/cm ³
Средний размер частиц	350	µm

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай



WeChat