

Polymist® F5A EX

Polytetrafluoroethylene

Solvay Specialty Polymers

Описание материалов:

Polymist® F5A EX is a white PTFE micronized powder PTFE micronized powder composed of discrete particles.

Designed for use in critical engineering and high end performance plastics applications, Polymist® F5A EX will improve wear resistance and reduce coefficient of friction.

Main features of Polymist® F5A EX are:

Better wear resistance

Increased pressure x velocity (PV) limits

Reduced friction

Improved stick-slip response

Improved mold release

Главная Информация			
Используется	Добавка		
Внешний вид	Белый		
Формы	Порошок		
Физический	Номинальное значение	Единица измерения	Метод испытания
Удельная площадь поверхности	3.0	m ² /g	Internal method
Средний размер частиц-D50	12	µm	Internal method
Плотность объема	500	g/l	ASTM D4895
Температура расплава	325 - 335	°C	ASTM D3418
Дополнительная информация	Номинальное значение	Единица измерения	Метод испытания

Storage and Handling

The usual precautions for safe storage and handling of Polymist® F5A EX should be taken according to material safety documentation and experience. There will be no chemical deterioration of the Polymist® F5A EX during proper storage.

Shelf life of Polymist® F5A EX micronized powders will vary depending upon whether the recommended storage conditions are maintained and whether the material remains free from foreign contamination during storage time (not exposed to dirt, dust, water or other chemicals). The material should remain sealed in the original containers and storage conditions should provide for protection from temperature extremes as well as rain, snow or other wet environments (or such conditions which may damage the storage containers in which the product is stored).

Safety and Toxicology

Before using Polymist® F5A EX PTFE micronized powders, consult the product Material Safety Data Sheet and follow all label directions and handling precautions.

As with all PTFE materials, handling and processing should only be carried out in well ventilated areas. Vapor extractor units should be installed above processing equipment. Fumes must not be inhaled and eye and skin contact ought to be avoided. In case of skin contact wash with soap and water. In case of eye contact flush with water immediately and seek medical help.

Do not smoke in areas contaminated with powder, vapor or fumes.

See Material Safety Data Sheet for detailed advice on waste disposal methods.

Packaging

Polymist® F5A EX is packaged in 25 kg nonreturnable drums. Each drum has two bag liners made of polyethylene resin.

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

