

Dugdale PVC Rigid Injection Molding Compound - Soil

Rigid Polyvinyl Chloride

Dugdale Plc

Описание материалов:

A calcium/zinc stabilised, medium impact, injection-moulding compound.

A general purpose compound suitable for a variety of mouldings, but particularly rainwater system fittings.

Opaque colours to customer's requirements. Some pigment combinations may compromise the weathering characteristics of this compound and should be discussed with Dugdale technical personnel.

Главная Информация			
Добавка	Стабилизатор из кальция и цинка		
Характеристики	Высокая жесткость		
	Средняя ударопрочность		
Используется	Фитинги		
	Общее назначение		
Внешний вид	Доступные цвета		
	Непрозрачный		
Формы	Гранулы		
Метод обработки	Литье под давлением		
Физический	Номинальное значение	Единица измерения	Метод испытания
Удельный вес	1.44	g/cm ³	BS 2782 620A
Тепловой	Номинальное значение	Единица измерения	Метод испытания
Викат Температура размягчения	79.0 to 81.0	°C	BS 2782 120B ¹

NOTE

1. Rate B (120°C/h), Loading 2 (50 N)

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519
Мобильный телефон: +86-13424755533
Email: sales@su-jiao.com
Адрес: Господин Чжао
Район Фэнсянь, Шанхай, Китай

