Geon™ Vinyl Flexible XV3645

Flexible Polyvinyl Chloride

PolyOne Corporation

Описание материалов:

Geon™Vinyl Flexible XV3645 is a flexible polyvinyl chloride product. It can be processed by extrusion or injection molding and is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific. Geon™The application fields of Vinyl Flexible XV3645 include hose and food contact applications. The main characteristics are: accessible food.

Главная Информация	
Характеристики	Соответствие пищевого контакта
Используется	Труба Фитинги для труб
Рейтинг агентства	FDA пищевой контакт, не Номинальный
Внешний вид	Прозрачный/прозрачный
Формы	Частицы
Метод обработки	Экструзия Литье под давлением

Физический	Номинальное значение	Единица измерения	Метод испытания
Удельный вес	1.22	g/cm³	ASTM D792
Твердость	**Номинальное значение**	**Единица измерения**	**Метод испытания**
Твердость дюрометра (Shore A, 10 sec)	78		ASTM D2240
Эластомеры	**Номинальное значение**	**Единица измерения**	**Метод испытания**
Tensile Stress (100% Strain)	10.3	MPa	ASTM D412
Прочность на растяжение (Break)	17.2	MPa	ASTM D412
Удлинение при растяжении (Break)	350	%	ASTM D412
Тепловой	**Номинальное значение**	**Единица измерения**	**Метод испытания**
Температура ломкости	-38.3	°C	ASTM D746

Дополнительная информация

□□:□□□21□□□□.□□□□□□,□□□“□□□□□□□□□□”.□□□□□□□□□□□□□□□□□□□

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

WeChat