

## Vinnolit® E 67 FF

Polyvinyl Chloride

Vinnolit GmbH & Co. KG

### Описание материалов:

PVC for paste making

@ Vinnolit E 67 FF is a fine particle size, low- medium molecular weight emulsion type PVC homopolymer with a medium emulsifier content. It produces plastisols exhibiting medium viscosity at low and high shear rates with essentially Newtonian flow properties with low plasticizer levels (40-60 phr). It has been particularly developed for low plasticizer content compact or chemically foamed formulations. It exhibits generally excellent gelation/fusion rates and gives good thermal/light stability with a wide range of stabilisers. The use of high speed type mixers is recommended.

Processing and Application:

Vinnolit E 67 FF produces plastisols with low plasticizer content which are ideal for the spread coating of chemically blown foams for cushioned flooring and wallcoverings using the "Congoleum" process, where a very fine closed cell structure with excellent inhibition and contour sharpness may be achieved at both high and low expansion levels. Plastisols can be applied by reverse-roll coaters, rotary screen coaters.

Главная Информация			
Добавка	Пластификатор		
Характеристики	Хорошая термическая стабильность		
	Гомополимер		
	Средняя вязкость		
	Пластифицированный		
Используется	Нанесение покрытия		
	Напольное покрытие		
	Стеновые панели		
Метод обработки	Обработка пены		
Физический	Номинальное значение	Единица измерения	Метод испытания
Видимая плотность	0.40	g/cm <sup>3</sup>	ISO 60
K-Value	67.0		ISO 1628-2
Viscosity Number (Reduced Viscosity)	113.0	ml/g	ISO 1628-2
Распределение размеров частиц <sup>1</sup>	< 0.20	%	ISO 1624
Летучее вещество	< 0.30	%	ISO 1269

### NOTE

1. retained on 0.063 mm screen

\* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

**Susheng Import & Export Trading Co.,Ltd.**

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

