

Tecnoflon® N 935

Fluoroelastomer

Solvay Specialty Polymers

Описание материалов:

Tecnoflon® N 935 is a medium high viscosity fluoroelastomer copolymer. Tecnoflon® N 935 is intended as a general purpose fluoroelastomer. It can be blended with other polymers of the Tecnoflon® family to meet specific requirements. Tecnoflon® N 935 does not contain curatives: therefore the proper levels of Tecnoflon® FOR M1 and Tecnoflon® FOR M2 must be added to achieve the required properties. It can be also cured with diamine based systems such as Tecnoflon® Tecnocin A and Tecnoflon® Tecnocin B.

Some of the unique properties of Tecnoflon® N 935 are:

Excellent compression set

Lack of mould fouling

Superior extrusion behaviour

Superior mould flow

Excellent mould release

Compliant to FDA 21,CFR 177.2600

Tecnoflon® N 935 can be used for compression moulding of O-rings, seals, gaskets and other items. The product can be mixed using typical fluoroelastomers compounding ingredients and mixing can be accomplished with two-roll mills or internal mixers. The material can be extruded into hoses or profiles and can be calendered to make sheet stocks or belting. Compounds based on Tecnoflon® N 935 can be dispersed in solvents for coating applications.

Finished goods can be produced by a variety of rubber processing methods.

Главная Информация

Характеристики	Сополимер Общее назначение Хороший поток Хороший выпуск пресс-формы Комплект низкого сжатия Средняя вязкость
Используется	Ремни/ремонт ремней Смешивание Прокладки Общее назначение Шланг Профили Уплотнения Лист
Рейтинг агентства	Управление по санитарному надзору за качеством пищевых продуктов и медикаментов 21 CFR 177,2600
Внешний вид	Полупрозрачный
Формы	Плита
Метод обработки	Каландрирование Уплотнение

Прессформа сжатия

Экструзия

Физический	Номинальное значение	Единица измерения
Вязкость Mooney ¹ (ML 1+10, 121 °C)	62	MU
Содержание фтора ²	66	%

NOTE

1. Raw polymer
2. Raw polymer

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай



WeChat