

Beamset 575

Polyurethane

Arakawa Chemical Industries, Ltd.

Описание материалов:

This resin is a photo-curable resin that quickly and three-dimensionally cures by radical polymerization that occurs with electron beam (EB) or ultraviolet ray (UV) irradiation. This resin has been used widely for various applications.

Type:

Urethane acrylate

Characteristics:

Good chemical resistance

Excellent hardness

Use:

Hard coatings

Главная Информация		
Характеристики	Хорошая химическая стойкость Высокая твердость	
Используется	Нанесение покрытия	
Внешний вид	Прозрачный-светло-желтый Желтый	
Формы	Жидкость	
Дополнительная информация	Номинальное значение	Единица измерения
Функциональность	3.00 to 6.00	
Нелетучее содержание	100	%
Uncured Properties	Номинальное значение	Единица измерения
Вязкость (25°C)	10 to 14	Pa·s

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

