

HTA® 240

Полиэфирное волокно

Ероху; Epoxide

Cytec Industries Inc.

Описание материалов:

HTA240 is a structural adhesive film suitable for the bonding of aluminium and composite substrates either to themselves or to honeycomb core materials. HTA240 offers a good combination of honeycomb peel strength and high service temperature capability, can be co-cured with Cytec's HTM® prepregs, and is capable of withstanding further secondary cures up to 180°C (356°F). HTA240 is fully compatible with MTM® 44-1 Out-of-Autoclave (OoA) prepregs and many other MTM40 series prepregs.

| Главная Информация | | | |
|---------------------------------|--|-------------------|-----------------|
| Наполнитель/армирование | Полиэфирное волокно | | |
| Характеристики | Хорошая прочность | | |
| | Термическое лечение | | |
| | Высокая термостойкость | | |
| Используется | Клеи | | |
| | Склеивание | | |
| | Детали конструкции | | |
| Формы | Пленка | | |
| Физический | Номинальное значение | Единица измерения | |
| Удельный вес ¹ | 1.30 | g/cm ³ | |
| Cured Properties | Номинальное значение | Единица измерения | Метод испытания |
| Lap Shear Strength ² | | | ASTM D3165 |
| 21°C | 32.0 | MPa | |
| 180°C | 14.0 | MPa | |
| NOTE | | | |
| 1. | Cured resin | | |
| 2. | Cured: 1 hour at 180°C (356°F), 2.1 bar (30psi) | | |

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

