

NORDEL™ IP 3760P

Hydrocarbon Rubber

The Dow Chemical Company

Описание материалов:

NORDEL™IP 3760P hydrocarbon rubber is an ethylene-propylene-diene terpolymer (EPDM) with medium viscosity and medium diene content. It has a moderate curing rate and is suitable for applications that require low modulus, good elongation, and heat resistance., Weather resistance. The supply form is transparent pellets. INSITE was used in the preparation of NORDEL IP 3760P.™technology.

Main features:

Medium crystallinity

Low diene content

high molecular weight

stable heat and ultraviolet resistance

Comply with the following regulations:

U.S. Food and Drug Administration Regulation 21 CFR 177.2600

U.S. Food and Drug Administration Regulation 21 CFR 175.1520 (see Note 1)

U.S. Food and Drug Administration Regulation 21 CFR 175.105 (see Note 2)

U.S. Food and Drug Administration Regulation 21 CFR 177.1210

Please check the regulations for complete details.

Application field:

Impact modification

Wires and cables

Peroxide-cured heat-resistant hose

remarks:

(1) can be used to contact all types of food, except oil emulsion water, high-fat or low-fat food, low-humidity fat and oil food.

(2) Adhesive only.

Главная Информация

Рейтинг агентства

Управление по санитарному надзору за качеством пищевых продуктов и медикаментов 21 CFR 175,105

Управление по санитарному надзору за качеством пищевых продуктов и медикаментов 21 CFR 175,1520

Управление по санитарному надзору за качеством пищевых продуктов и медикаментов 21 CFR 177,1210

Управление по санитарному надзору за качеством пищевых продуктов и медикаментов 21 CFR 177,2600

Формы

Частица 2

Физический	Номинальное значение	Единица измерения	Метод испытания
Удельный вес	0.870	g/cm ³	ASTM D297
Вязкость Mooney (ML 1+4, 125°C)	63	MU	ASTM D1646
Ethylene Content	67.0	wt%	ASTM D3900
Содержание этилидена норборнена (ENB)	2.2	wt%	ASTM D6047
Содержание пропилена	32.0	wt%	ASTM D3900
Молекулярное распределение веса	medium		Internal method
Летучее вещество		wt%	Internal method

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

