

Lusin® Clean 1061

Thermoplastic

Chem-Trend L.P.

Описание материалов:

Ready-to-use Purging Compound for Screw, Barrel, Nozzle and Hot-runner of Thermoplastic Injection Moulding Machines

Benefits

Especially developed for caps and closures made of polyolefin

Rapid cleaning effect

Suitable for hot-runner systems

Suitable as freezing mixture

According to FDA regulations (21 CFR) all components of the formulation of Lusin® Clean 1061 are either GRAS or permitted for direct or indirect food contact

The formulation of Lusin® Clean 1061 is in compliance with European Plastics Regulation No 10/2011

Description

Lusin® Clean 1061 is a ready to use granular purging compound for screw, barrel, nozzle and hot-runner of injection moulding machines processing thermoplastic resins. The purging compound consists of high quality thermoplastic resins as well as highly efficient cleaning additives and does not contain abrasives. Lusin® Clean 1061 is especially recommended for color or material change as well as for the removal of black spots, carbon residues and cracked materials and can be used at processing temperatures up to 290°C (554°F). Lusin® Clean 1061 can also be used as freezing mixture for shutdown procedures during the weekend.

Typical properties

Appearance : translucent yellow granules

Softening point : approx. 145°C

Главная Информация	
Добавка	Неуказанные добавки
Используется	Очистительная смесь
Рейтинг агентства	FDA GRAS (общепризнанный как безопасный) FDA пищевой контакт, не Номинальный Европа без 10/2011
Внешний вид	Полупрозрачный Желтый
Формы	Частицы

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

