

## Dyna-Purge® C

Proprietary

Dyna-Purge, division of Shuman Plastics

### Описание материалов:

Designed for Clear and Transparent Resins

DYNA-PURGE C is a clear, non-abrasive, non-chemical engineered thermoplastic purging compound, formulated to purge high clarity resins such as PET, GPPS, PC, SAN and PMMA. A proprietary additive expands allowing for the purge to reach and clean all areas of the machine. The carrier matrix then flushes away the previous resin and other impurities, eliminating any "milky drag" or residue.

#### FEATURES & BENEFITS:

Excellent for transition to clear or transparent resin, preventative machine maintenance, and before manual cleaning

Excellent for purging through hot runner systems, dies, or other downstream equipment

Effective through a wide temperature range 380°F-590°F(193°C-310°C)

Easy to use - no process adjustment necessary - use at the resident resin processing temperature and RPM speed

Non-abrasive thermoplastic, which thoroughly loosens carbonized and degraded resin, allowing it to be flushed out of the system

Safe, non-hazardous, with no chemicals - ingredients are FDA compliant

Heat stable - recommended during shutdown and start-up

Low "cost-per-purge" - only small quantity needed to be effective

No mixing required - simply use "as is"

Unlimited shelf life

### Главная Информация

Используется	Очистительная смесь
Рейтинг агентства	FDA не рассчитан
Формы	Частицы
Метод обработки	Выдвунное формование Экструзионная смесь Экструзия Экструзионный лист Экструзионное формование профиля Литье под давлением

### Дополнительная информация

Applications:

Injection - cold and hot runners

Extrusion - profile, sheet, compounding, blow molding

Temperature Range: 380 - 590°F (193 - 310°C)

Types of Resins: PET, GPPS, PC, SAN, PMMA as well as other clear and transparent resins

Minimum Clearance: None

Amount of Purge: 1 to 2 times barrel capacity (actual amount needed depends on machine conditions)

\* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

## Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

