Escorene™ Ultra UL 7710 Series

Ethylene Vinyl Acetate Copolymer Resin

ExxonMobil Chemical

Описание материалов:

Escorene Ultra UL 7710 is a high-fluidity copolymer containing 26.7% vinyl acetate, which is well compatible with hydrocarbon tackifiers and most waxes. It is suitable for manufacturing hot melt adhesives, sealants and mixed waxes. The additives contained in UL 7710E can improve the fluidity and operability of particles.

Главная Информация			
Добавка	UL 7710E: стабилизатор тепла UL 7710: стабилизатор тепла		
Формы	Частицы		
Физический	**Номинальное значение**	**Единица измерения**	**Метод испытания**
Плотность	0.941	g/cm³	ASTM D1505
Массовый расход расплава (MFR) (190°C/2.16 kg)	420	g/10 min	ASTM D1238
Содержание винилацетата	26.7	wt%	ExxonMobil Method
Твердость	**Номинальное значение**	**Единица измерения**	**Метод испытания**
Твердость дюрометра (Shore A, 15 sec)	60		ASTM D2240
Механические	**Номинальное значение**	**Единица измерения**	**Метод испытания**
Прочность на растяжение (Break)	1.59	MPa	ASTM D638
Удлинение при растяжении (Break)	500	%	ASTM D638
Флекторный модуль-1% Secant	13.0	MPa	ASTM D790

Юридическое заявление

□□□□□□□□□□□□□,□□□□□□□□□□□□□

WeChat