

BJB Polyurethane SC-80

Polyurethane Thermoset Elastomer

BJB Enterprises, Inc.

Описание материалов:

SC-80 is a single component aliphatic polyurethane which fully reacts using water as its dispersing agent. Originally developed as a primer for painting flexible polyurethane materials, the SC-80 is often used as a top-coat or a product that will seal porous substrates.

Tough yet flexible film

Low temperature flexibility

Excellent water resistance

Easy to pigment with water-based pigments

Главная Информация			
Характеристики	Хорошая цветность		
	Хорошая гибкость		
	Гибкость при низкой температуре		
	Низкое поглощение воды		
	Сверхвысокая прочность		
Используется	Нанесение покрытия		
	Пленка		
	Краска		
	Герметики		
Внешний вид	Прозрачный янтарь		
Формы	Жидкость		
Метод обработки	Распыление		
Физический	Номинальное значение	Единица измерения	
Удельный вес	1.01	g/cm ³	
Термокомплект	Номинальное значение	Единица измерения	Метод испытания
Терморегулирующая вязкость ¹ (25°C)	20.0	cP	ASTM D2393
Dry Time ² (25°C)	3.0	hr	
NOTE			
1.	Mixed, Brookfield		
2.	3 mil wet film on glass		

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

