

Ketjenflex® 6

Plasticizer Additive

Axcentive SARL

Описание материалов:

KETJENFLEX® 6 is a toluene sulfonamide based plasticizer used in Plastics, Inks, Adhesives and Coatings.

Description and Application

KETJENFLEX® 6 is used as a special plasticizer in Plastics, Ink, Adhesive and Coating formulations. KETJENFLEX® 6 effectively plasticizes many resin systems including nitrocellulose, polyamide, PVAC, rosin, epoxy, polyurethane, cellulose acetate and various biopolymers.

Another area of use is as starting material in the preparation melamine/urea formaldehyde based laminates as well as reactive plasticizer in epoxy and polyurethane resins.

KETJENFLEX® 6 is used up to 5g/l as brightening agent in metal plating processes reducing tensile stress and improving brightness and gloss.

Главная Информация		
Additives Physical	Номинальное значение	Единица измерения
Bulk Density	730 to 760	kg/m ³
Additive Concentration	> 100	%
State at Room Temperature	Solid	
Chemical Description	Toluene Sulfonamide	

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

