

Hifax TYC 337P 3 S81466

15% тальк

Polypropylene Copolymer

LyondellBasell Industries

Описание материалов:

Hifax TYC 337P 3 S81466 is a 15% talc filled PP copolymer, with very high melt flow rate and good impact resistance. Product is available as a customized color matched, pellet form. This grade is delivered in S81466 color version.

This grade is not intended for medical, pharmaceutical, food and drinking water applications.

Главная Информация			
Наполнитель/армирование	Тальк наполнитель, 15% наполнитель по весу		
Характеристики	Сополимер Хорошая ударопрочность Высокая яркость		
Используется	Наружное применение		
Внешний вид	Доступные цвета		
Формы	Частицы		
Метод обработки	Литье под давлением		
Физический	Номинальное значение	Единица измерения	Метод испытания
Плотность (23°C)	0.990	g/cm ³	ISO 1183/A
Массовый расход расплава (MFR) (230°C/2.16 kg)	36	g/10 min	ISO 1133
Механические	Номинальное значение	Единица измерения	Метод испытания
Флекторный модуль ¹ (23°C)	1300	MPa	ISO 178/A
NOTE			
1.	1.0 mm/min		

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай



WeChat