

Yanshan PE LD104

Low Density Polyethylene

SINOPEC Beijing Yanshan Petrochemical

Описание материалов:

Yanshan PE LD104 is a Low Density Polyethylene product. It can be processed by film extrusion and is available in Asia Pacific. Applications of Yanshan PE LD104 include film, bags/liners, coating applications, medical/healthcare and wire & cable. Primary characteristic: crosslinkable.

Главная Информация			
Характеристики	Crosslinkable		
Используется	Сумки		
	Кабельный кожух		
	Пленка		
	Ламинаты		
	Медицинская упаковка		
	Многослойная пленка		
	Термоусадочная пленка		
Метод обработки	Экструзионная пленка		
Физический	Номинальное значение	Единица измерения	Метод испытания
Плотность	0.925	g/cm³	ASTM D1505
Массовый расход расплава (MFR)	2.0	g/10 min	ASTM D1238
Механические	Номинальное значение	Единица измерения	Метод испытания
Прочность на растяжение (Yield)	10.0	MPa	ASTM D638
Удлинение при растяжении (Break)	400	%	ASTM D638
Дополнительная информация	Номинальное значение	Единица измерения	
Fish Eye (0.300 to 2.00 mm)	30.0	n/1200 cm ³	
В полоску (> 1.00 сm)	20.0	cm/20 m ³	

^{*} Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com Адрес: Господин Чжао Район Фэнсянь, Шанхай, Китай



