Exxelor™ VA 1202

Polymer Resin

ExxonMobil Chemical

Описание материалов:

Exxelor VA 1202 polymer resin is a maleic anhydride functionalized low viscosity ethylene copolymer produced by reactive extrusion technology. Its fully saturated main chain brings excellent thermal and oxidative stability, resulting in better weather resistance.
This brand is designed for:
ultra-tough nylon applications without low temperature impact resistance requirements.
medium/low toughness applications.
impact improvement application of glass fiber filling.

Главная Информация			
Физический	**Номинальное значение**	**Единица измерения**	**Метод испытания**
Массовый расход расплава (MFR) (230°C/5.0 kg)	17	g/10 min	ASTM D1238, ISO 1133
Оптический	**Номинальное значение**	**Единица измерения**	**Метод испытания**
Yellowness Index	< 20	YI	ASTM E313

Дополнительная информация

□□□□□:□□□“□□□□□□□”□□□□□□□□□□□□□□□□□□□.□□□□□□□□□□,□□□□□□□□□□□,□□□□ 25 □□□(□□□□ 50 □),450 □□□□□□ 1 □□□□.

Юридическое заявление

□□□□□□□□□□□□□,□□□□□□□□□□□□,□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□,□□□□□□□.

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

WeChat