ExxonMobil™ LDPE LD 202.48

Low Density Polyethylene Resin

ExxonMobil Chemical

Описание материалов:

LD 202.48 is a low density polyethylene extrusion coating brand, especially for high-speed, light-weight extrusion coating development: high-speed processability, good heat sealing performance, LD 202.48 has good coating on non-woven fabric substrate. The high melting index and low density of this brand make it have a good balance between non-woven fabric surface adhesion and flexibility after coating.

Главная Информация			
Формы	Частицы		
Физический	**Номинальное значение**	**Единица измерения**	**Метод испытания**
Массовый расход расплава (MFR) (190°C/2.16 kg)	12	g/10 min	ASTM D1238
Тепловой	**Номинальное значение**	**Единица измерения**	**Метод испытания**
Викат Температура размягчения	84.0	°C	ASTM D1525
Юридическое заявление			

□□□□□□□□□□□□□□□(□□:FDA,EU,HPFB),□□□□□□□□□□□□□□□□□□.□□□□□□□□□□□□□□,□□□□□□□□□□□□□□

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

WeChat