

## Polymist® XPP 548

Polytetrafluoroethylene

Solvay Specialty Polymers

### Описание материалов:

Polymist® XPP 548 is a grey PTFE micronized powder composed of discrete particles.

Designed for use in critical engineering and high end performance Coatings and Inks, Polymist® XPP 548 will improve non-stick properties and mar and abrasion resistance as well as slip and rub resistance.

Main Polymist® XPP 548 features are:

Improved abrasion, scratch and rub resistance

Increased slip and surface lubricity

Reduced blocking

Better chemical resistance

Increased temperature resistance

Gloss retention

Главная Информация			
Используется	Добавка		
Внешний вид	Серый		
Формы	Порошок		
Физический	Номинальное значение	Единица измерения	Метод испытания
Удельная площадь поверхности	3.0	m <sup>2</sup> /g	Internal method
	20.0		
Размер частиц-(D50/D99)	4.00	µm	Internal method
Плотность объема	> 400	g/l	ASTM D4895
Масляная шлифовка-Нпири	2.50		NPIRI
Температура расплава	315 - 325	°C	ASTM D3418
Дополнительная информация	Номинальное значение	Единица измерения	Метод испытания

## Processing

Polymist® XPP 548 is used as additives in paints and coatings where improvements in non-stick, mar resistance, slip, chemical resistance, and moisture repelling characteristics are desired.

Polymist® XPP 548 may be used independently as an additive or in combination with polyethylene waxes. The PTFE content at the surface layer is required in order to impart the properties of PTFE to the coating, substantially. Extreme environmental demands on greases, such as those experienced in the automotive industry (i.e. wide temperature ranges and heavy loads) can be accommodated by the addition of Polymist® XPP 548 micronized powders.

Polymist® XPP 548 can be dispersed easily at room temperature, and it doesn't agglomerate at temperatures used during formulation or printing. Chemical inertness and improved temperature resistance give ink formulators the opportunity to use a variety of solvents without adverse chemical reactions.

## Storage and Handling

The usual precautions for safe storage and handling of Polymist® XPP 548 should be taken according to material safety documentation and experience. There will be no chemical deterioration of the Polymist® XPP 548 during proper storage.

Shelf life of Polymist® XPP 548 micronized powders will vary depending upon whether the recommended storage conditions are maintained and whether the material remains free from foreign contamination during storage time (not exposed to dirt, dust, water or other chemicals). The material should remain sealed in the original containers and storage conditions should provide for protection from temperature extremes as well as rain, snow or other wet environments (or such conditions which may damage the storage containers in which the product is stored).

## Safety and Toxicology

Before using PTFE Polymist® XPP 548 micronized powders consult the product Material Safety Data Sheet and follow all label directions and handling precautions.

As with all PTFE materials, handling and processing should only be carried out in well ventilated areas. Vapor extractor units should be installed above processing equipment. Fumes must not be inhaled and eye and skin contact ought to be avoided. In case of skin contact wash with soap and water. In case of eye contact flush with water immediately and seek medical help. Do not smoke in areas contaminated with powder, vapor or fumes. See Material Safety Data Sheet for detailed advice on waste disposal methods.

## Packaging

Polymist® XPP 548 is packaged in 25 kg non returnable drums. Each drum has one bag liner made of polyethylene resin.

\* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

СВЯЖИТЕСЬ С НАМИ

## Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

