

## NANCAR® 1072CG

Acrylonitrile Butadiene Rubber

Nantex Industry Co., Ltd.

### Описание материалов:

NANCAR® 1072CG is a copolymer of butadiene and acrylonitrile of medium high oil resistance, specifically designed to contain free carboxylic groups and is soluble in MEK without mill breakdown. Sufficient antioxidant is added during manufacture for normal aging conditions.

NANCAR® 1072CG is used for adhesive and coating applications. Modifying resins.

Главная Информация			
Добавка	Антиоксидант		
Характеристики	Сополимер		
	Маслостойкий		
Используется	Клеи		
	Нанесение покрытия		
Формы	Гранулы		
Физический	Номинальное значение	Единица измерения	Метод испытания
Удельный вес	1.00	g/cm <sup>3</sup>	
Вязкость Mooney (ML 1+4, 100°C)	34	MU	ASTM D1646
Содержание акрилонитрила-Скрепленный	27.0	%	Internal Method
Содержание золы	0.40	%	Internal Method
Содержание геля	gel free		Internal Method
Вязкость-Необработанная вязкость цемента, 20% в MEK	700	mPa·s	Internal Method
Потеря тепла	0.30	%	ASTM D5688

\* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

### Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

