Maxxam™ FR PE CONC 1 NAT

Low Density Polyethylene

PolyOne Corporation

Описание материалов:

Maxxam™FR flame retardant polyolefin polymers and masterbatches meet the strict flammability requirements set by the industry, including UL 94V-2,V-0 and 5VA performance grades of UL Laboratory. In addition, the various polymers in the Maxxam FR combination are also suitable for high relative temperature index (RTI) levels.

Главная Информация			
Характеристики	Огнестойкий		
Формы	Частицы		
Физический	**Номинальное значение**	**Единица измерения**	**Метод испытания**
Удельный вес	1.58	g/cm³	ASTM D792
Массовый расход расплава (MFR) [1] (190°C/2.16 kg)	2.0 - 5.0	g/10 min	ASTM D1238

Дополнительная информация

MAXXAM FR PO □□ 62□□□□□□□□□□□□□□□□□□□□. □□□□□□□□□□,□□□□□□□□□□□□□□□□□□□□.□□□□□□□□□□:4-7□(□□)□□□□□□,5□(□□)□□□□□□- □1□Concentrate 62.□□□□□□□□□□□□,□□□□□□□□□UL-94 V-2□VTM-2□□□□□□□□.□LDPE □□ @ 4-8 mil □□□□8% PO CONC 62□□□BFD IX-1□NFPA 701□□□□ / □□□□□□□1.5mm□PE @ 15-30%□□□□V-2□□□□.□□□□□□□□□□.

NOTE	
1.	Procedure A

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

WeChat