

Lusin® Alro OL 153 S

Silicone

Chem-Trend L.P.

Описание материалов:

Universal Silicone Release Agent for Processing Thermoplastic Resins and Elastomers

Benefits

Suitable for mould temperatures up to 150°C (302°F)

easy and multiple demoulding

wide range of application

can also be used as a lubricant

Description

Lusin® Alro OL 153 S is an universal release agent for the demoulding of thermoplastic, thermoset and elastomeric parts up to a mould temperature of 150°C (302°F). It is also suitable as a lubricating agent with improved anti-friction properties.

Lusin® Alro OL 153 S is based on non-reactive silicone oils which are absolutely colourless and have no smell.

Typical Properties

Appearance of the active ingredient : Liquid, colourless

Application

A fine even spray film should be applied to the clean mould; especially to edges and undercuts. For cleaning we recommend the use of Lusin® L 21 F as mould cleaning agent and Lusin® Clean L 11 or Lusin® Clean L 51 as degreasing agent.

In terms of post treatment of the produced parts we do not recommend the use of Lusin® Alro OL 153 S. The high demoulding and wetting properties even in low concentrations will cause surface defects of the post treatment agent.

Главная Информация	
Внешний вид	Бесцветный
Формы	Жидкость

^{*} Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

