

ALKAMIX™ MB-PA505

Fluoropolymer

Marplex Australia Pty. Ltd.

Описание материалов:

ALKAMIX™ MB-PA505 is a processing aid masterbatch based on a fluoropolymer compound at a concentration of 2 percent. ALKAMIX™ MB-PA505 can be added to linear low density polyethylene (LLDPE) during extrusion to eliminate melt fracture ("Sharkskin") type extrusion defects. The level required will vary according to extrusion equipment and type of LLDPE being used, however the recommended addition level is between 1 and 3 percent. ALKAMIX MB-PA505 is compatible with the process aid used in "Alkatuff" film polymers. The maximum level of addition of ALKAMIX™ MB-PA505 based on both good manufacturing practice and to ensure conformance to the requirements to the United States Food and Drug Administration Regulations CFR21 is 10 percent, when added to a polyethylene formulation free of any other additives. The suitability of finished articles manufactured using this material as a component, and the observance of given limitations, must be verified by the converter for each application to ensure compliance with all relevant regulations. An overall migration limit may apply to the finished article.

Главная Информация

Добавка	Обработка помощи (2%)				
Используется	Маточная смесь				
Физический	Номинальное значение	Единица измерения	Метод испытания		
Плотность	0.935	g/cm ³	ASTM D1505		
Инъекция	Номинальное значение	Единица измерения			
Температура обработки (расплава)	< 200	°C			

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай



WeChat