

## Altuglas® BS 580

Polymethyl Methacrylate Acrylic

Altuglas International of Arkema Inc.

### Описание материалов:

ALTUGLAS®BS 580 is a methacryliccopolymer of medium molecular weight with good solubility and fluidity, available in the form of solid beads. ALTUGLAS®BS 580 has a good range of application as Inclusions, Acrylic Composites and Binder in solvent coatings. Use of ALTUGLAS®BS 580 in compounding to make acrylic Master-batches is highly suggested.

Главная Информация		
Характеристики	Сополимер Хороший поток Средний Молекулярный вес	
Используется	Связыватель Нанесение покрытия Уплотнение Маточная смесь	
Формы	Сферы	
Физический	Номинальное значение	Единица измерения
Видимая плотность	0.70	g/cm <sup>3</sup>
Массовый расход расплава (MFR) (230°C/3.8 kg)	5.0	g/10 min
Кислотная ценность	< 1.00	mg KOH/g
Внутренняя вязкость	0.48 to 0.50	dl/g
Размер частиц	150 to 200	µm
Вязкость-Растворитель (30% w MEK)	500	mPa·s
Остаточный мономер	< 0.35	%
Испарители	< 1.5	%
Тепловой	Номинальное значение	Единица измерения
Температура перехода стекла	104	°C

\* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

**Susheng Import & Export Trading Co.,Ltd.**

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

