

ALKAMIX™ MB6005

Linear Low Density Polyethylene

Qenos Pty Ltd

Описание материалов:

ALKAMIX MB6005 is a combined slip and antiblock masterbatch based on a linear low density polyethylene carrier. It is formulated with slip additive (Erucamide) at a concentration of 8 percent and antiblock additive at a concentration of 25 percent.

ALKAMIX MB6005 can be added to linear low density polyethylene (LLDPE) during extrusion to reduce film blocking and coefficient of friction. The level required will vary according to desired properties and presence of any other additives, however the recommended addition level is between 1 and 2 percent.

The maximum level of addition of MB6005 based on both good manufacturing practice and to ensure conformance to the requirements to the United States Food and Drug Administration Regulations CFR21 is 2.5 percent, when added to a polyethylene formulation free of any other additives.

Главная Информация

Добавка	Антиблок (25%)
	Скольжения (8%)
Характеристики	Антиблокировка
	Комбинация
Используется	Смешивание
Формы	Гранулы

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай



WeChat